KOMBIC 100 SURFACE



K11SF1523RF940NBW

KOMBIC 100 SF 1500 IP23 9NW RF FL BK/WH

Description:

Finish: Matte black RAL 9011

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.416 lm °K: 4000 Plum: 14,1W CRI: 90 Efficacy: 100,4 lm/w R9: 65 UGR: <19

3 MacAdam: Type: СОВ

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power Supply:

220-240V 50/60Hz

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE




K11SF1523RF940NBW


KOMBIC 100 SF 1500 IP23 9NW RF FL BK/WH


PHOTOMETRIC DATA:


K11SF1523RF940NBW $\eta = 100\%$ Imax = 2279 cd/klm UTE:


CIE: 100 100 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH