KOMBIC 100 SURFACE

K11SF1523RF940NWW



KOMBIC 100 SF 1500 IP23 9NW RF FL WH/WH

Description:

Suspended or ceiling mounting downlight model KOMBIC 100 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP23 degree of protection. Group 0 photobiological safety. Reflector aluminium Flood to achieve a controlled light distribution. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface



TECHNICAL SPECIFICATIONS:

Light output: 1.474 lm °K: 4000 Plum: 14,1W CRI: 90 Efficacy: 104,5 lm/w R9: 65 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

13W Power:

Light output tolerance +/- 10%































CUSTOM MADE OPTIONS:















KOMBIC 100 SURFACE




K11SF1523RF940NWW


KOMBIC 100 SF 1500 IP23 9NW RF FL WH/WH


PHOTOMETRIC DATA:


K11SF1523RF940NWW $\eta = 100\%$ Imax = 2200 cd/klm UTE:


CIE: 98 99 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH