KOMBIC 100 SURFACE



K11SF1523RW927NWB

- KOMBIC 100 SF 1500 IP23 9VWW RF WFL W/B

Description:

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.264 lm °K: 2700 Plum: 14,1W CRI: 90 Efficacy: 89,6 lm/w R9: 58 Type: СОВ MacAdam: 3

LED Lifetime: 50.000 L80 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 13W Gear: Electronic

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF1523RW927NWB

KOMBIC 100 SF 1500 IP23 9VWW RF WFL W/B


PHOTOMETRIC DATA:


K11SF1523RW927NWB $\eta = 100\%$


Imax = 1215 cd/klm


UTE: 1,00A


CIE: 94 97 99 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH