KOMBIC 100 SURFACE

LAMP
Worktitude for light

K11SF1523RW927NWW **-** **KOMBIC 100 SF 1500 IP23 9VWW RF WFL W/W**

Description:

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	1.264 lm	**ºK :**	2700
Plum:	14,1W	**CRI :**	90
Efficacy:	89,6 lm/w	**R9 :**	58
Type:	COB	**MacAdam:**	3
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	**Power Supply:**	220-240V 50/60Hz
Power:	13W	**Gear:**	Electronic

Light output tolerance +/- 10%

EPD

K11SF1523RW927NWW   KOMBIC 100 SF 1500 IP23 9VWW RF WFL W/W

PHOTOMETRIC DATA :

K11SF1523RW927NWW

η = 100%

Imax = 1215 cd/klm

UTE: 1,00A

CIE: 94 97 99 100 100

180°

90°   90°

0°

alpha = 59,8°

	BACK	FRONT
100%		
75%	**49,9 %**	**49,9 %**
50%		
25%		

-8H -4H 0H 4H 8H

Melanopic Lux Ratio: 0.504

3000K 2500K 2000K
4000K   1667K
6000K
10000K

Rf
140
130 1 - Limits on the Planckian locus
120
110
100   Rg
90
80 2 - Limits for practical sources
70   **Rf 91.6 - Rg 99.6**
60
50 60 70 80 90 100

Tel.   +34937366800

Web   www.lamp.es

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU

12-03-2025

Pág.   2 / 3

ACCESORIES :

Suspension

Product code:

K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH

Tel. +34937366800

Web www.lamp.es

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU

12-03-2025

Pág. 3 / 3