KOMBIC 100 SURFACE



K11SF1523RW930NMW

- KOMBIC 100 SF 1500 IP23 9WW RF WFL MA/WH

Description:

Finish: metalized polycarbonate mate

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.318 lm °K: 3000 Plum: 14,1W CRI: 90 Efficacy: 93,5 lm/w R9: 53 Type: СОВ MacAdam: 3

LED Lifetime: 50.000 L80 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 13W Gear: Electronic

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF1523RW930NMW

KOMBIC 100 SF 1500 IP23 9WW RF WFL MA/WH


PHOTOMETRIC DATA:


K11SF1523RW930NMW $\eta = 100\%$


Imax = 1215 cd/klm


UTE: 1,00A


CIE: 94 97 99 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH