

KOMBIC 100 SURFACE


K11SF1540OP927NMW




KOMBIC 100 SF 1500 IP43 9VWW OP MA/WH

Description:

Suspended or ceiling mounting downlight model KOMBIC 100 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate**Weight:** 498 g**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

Light output:	1.135 lm	°K :	2700
Plum:	13,7W	CRI :	90
Efficacy:	82,9 lm/w	R9 :	62
Type:	COB	MacAdam:	3
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	12W	Gear:	Electronic

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

KOMBIC 100 SURFACE

K11SF1540OP927NMW

KOMBIC 100 SF 1500 IP43 9VWW OP MA/WH

PHOTOMETRIC DATA :

