KOMBIC 100 SURFACE

K11SF1540OP927NRW



KOMBIC 100 SF 1500 IP43 9VWW OP BR/WH

Description:

Suspended or ceiling mounting downlight model KOMBIC 100 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metalized interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K, CRI90 and Ra greater than 50. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: BRILLIANT METALLIC POLYCARBONATE

Weight: 498 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.205 lm °K: 2700 Plum: 13,7W CRI: 90 Efficacy: 88 lm/w R9: 62 Type: СОВ MacAdam: 3

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 12W Electronic

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:



















KOMBIC 100 SURFACE




K11SF1540OP927NRW


KOMBIC 100 SF 1500 IP43 9VWW OP BR/WH


PHOTOMETRIC DATA:


K11SF1540OP927NRW η = 100% lmax = 974 cd/klmUTE: 1,00A

CIE: 88 100 100 100 100









KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH