KOMBIC 100 SURFACE



K11SF1540WF940NWB

- KOMBIC 100 SF 1500 IP43 9NW WFL WH/BK

Description:

Finish: Matte white RAL 9010

TECHNICAL SPECIFICATIONS:

 Light output:
 1.134 lm
 °K:
 4000

 Plum:
 10W
 CRI:
 90

 Efficacy:
 113,4 lm/w
 R9:
 59

UGR: <19 **Power Supply:** 220-240V 50/60Hz

LED Lifetime: >100.000h L90 B10 (Ta=25°C)

Power: 8,5W

Light output tolerance +/- 10%

IP 43

EPD

CUSTOM MADE OPTIONS:























KOMBIC 100 SURFACE



K11SF1540WF940NWB


KOMBIC 100 SF 1500 IP43 9NW WFL WH/BK


PHOTOMETRIC DATA:


K11SF1540WF940NWB η = 100% Imax = 1239 cd/klm


UTE: 1,00A


CIE: 96 99 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

Description: K11SUADLATBK

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH