KOMBIC 100 SURFACE



K11SF2023RF830DBB

- KOMBIC 100 SF 2000 IP23 WW RF FL DA B/B

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.549 lm °K: 3000 Plum: 13,9W CRI: 80 Efficacy: 111,4 lm/w R9: 80 UGR: <19 3 MacAdam:

Type: COB Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE





K11SF2023RF830DBB


KOMBIC 100 SF 2000 IP23 WW RF FL DA B/B

PHOTOMETRIC DATA:

K11SF2023RF830DBB η = 100% Imax = 2279 cd/klm UTE: CIE: 100 100 100 100 100







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH