KOMBIC 100 SURFACE

K11SF2023RF927NMB

- KOMBIC 100 SF 2000 IP23 9VWW RF FL MA/BK

Description:

Finish: metalized polycarbonate mate Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	1.815 lm	٩ Κ :	2700
Plum:	21,6W	CRI :	90
Efficacy:	79,2 lm/w	R9 :	58
UGR:	<19	MacAdam:	3
Туре:	СОВ	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L70 B10 (Ta=25⁰C)	Gear:	Electronic
Power:	13W		

Light output tolerance +/- 10%

EPD


Worktitude for light


KOMBIC 100 SURFACE

K11SF2023RF927NMB

KOMBIC 100 SF 2000 IP23 9VWW RF FL MA/BK







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Worktitude for light

Product datasheet

KOMBIC 100 SURFACE

ACCESORIES :

Suspension



Product code: K11SUADLATBK

Description: KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH

Description: KOMBIC 100 SF ADAPT. LATERAL CABLE WH

Worktitude for light