KOMBIC 100 SURFACE



K11SF2023RF927NWB

- KOMBIC 100 SF 2000 IP23 9VWW RF FL WH/BK

Description:

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.815 lm °K: 2700 Plum: 21,6W CRI: 90 Efficacy: 84 lm/w R9: 58 UGR: <19 MacAdam: 3

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Electronic

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE




K11SF2023RF927NWB


KOMBIC 100 SF 2000 IP23 9VWW RF FL WH/BK


PHOTOMETRIC DATA:


K11SF2023RF927NWB $\eta = 100\%$ Imax = 2200 cd/klm UTE:


CIE: 98 99 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH