KOMBIC 100 SURFACE



K11SF2023RF930DBB

- KOMBIC 100 SF 2000 IP23 9WW RF FL DA B/B

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.785 lm
 % :
 3000

 Plum:
 20W
 CRI :
 90

 Efficacy:
 84 lm/w
 MacAdam:
 3

 UGR:
 <19</th>
 Power Supply:
 220-240V 50/60Hz

 Type:
 COB
 Gear:
 Adjustable DALI

LED Lifetime: 50.000 L70 B10 (Ta=25°C)

Power: 19W

Light output tolerance +/- 10%



Tel. +34937366800 Web www.lamp.es

KOMBIC 100 SURFACE




K11SF2023RF930DBB


KOMBIC 100 SF 2000 IP23 9WW RF FL DA B/B


PHOTOMETRIC DATA:


K11SF2023RF930DBB $_{\eta}$ = 100% Imax = 2279 cd/klm UTE:


CIE: 100 100 100 100 100




















Data according to regulations 2019/2020/EU and 2019/2015/EU

KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH