KOMBIC 100 SURFACE



K11SF2023RF930NWB

KOMBIC 100 SF 2000 IP23 9WW RF FL WH/BK

Description:

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.893 lm °K: 3000 Plum: 21,6W CRI: 90 Efficacy: 87,6 lm/w MacAdam: 3

UGR: <19 Power Supply: 220-240V 50/60Hz Type: СОВ

Gear:

Electronic

LED Lifetime: 50.000 L70 B10 (Ta=25°C)

Power: 13W

Light output tolerance +/- 10%

EPD

Data according to regulations 2019/2020/EU and 2019/2015/EU

KOMBIC 100 SURFACE




K11SF2023RF930NWB


KOMBIC 100 SF 2000 IP23 9WW RF FL WH/BK


PHOTOMETRIC DATA:


K11SF2023RF930NWB $_{\eta}$ = 100% Imax = 2200 cd/klm UTE:


CIE: 98 99 100 100 100




















Data according to regulations 2019/2020/EU and 2019/2015/EU

KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH