KOMBIC 100 SURFACE



K11SF2023RF940NBB

- KOMBIC 100 SF 2000 IP23 9NW RF FL BK/BK

Description:

Finish: Matte black RAL 9011

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.903 lm
 ⁰K :
 4000

 Plum:
 21,6W
 CRI :
 90

 Efficacy:
 100,9 lm/w
 R9 :
 65

 UGR:
 <19</td>
 MacAdam:
 3

 UGR:
 <19</th>
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Electronic

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE




K11SF2023RF940NBB


KOMBIC 100 SF 2000 IP23 9NW RF FL BK/BK


PHOTOMETRIC DATA:


K11SF2023RF940NBB $_{\eta}$ = 100% Imax = 2279 cd/klm UTE:


CIE: 100 100 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH