KOMBIC 100 SURFACE



K11SF2023RW830DMB

- KOMBIC 100 SF 2000 IP23 WW RF WFL DA M/B

Description:

Finish: metalized polycarbonate mate

Weight: 712 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.538 lm
 ⁰K :
 3000

 Plum:
 13,9W
 CRI :
 80

 Efficacy:
 110,6 lm/w
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF2023RW830DMB

KOMBIC 100 SF 2000 IP23 WW RF WFL DA M/B


PHOTOMETRIC DATA:


K11SF2023RW830DMB $_{\eta} = 100\%$ $Imax = 1215 \ cd/kIm$


CIE: 94 97 99 100 100



UTE: 1,00A







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH