KOMBIC 100 SURFACE



K11SF2023RW830NBW

- KOMBIC 100 SF 2000 IP23 WW RF WFL BK/WH

Description:

Finish: Matte black RAL 9011

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.421 lm
 % :
 3000

 Plum:
 14,1W
 CRI :
 80

 Efficacy:
 100,7 lm/w
 MacAdam:
 3

UGR: <19 **Power Supply:** 220-240V 50/60Hz

Gear:

Electronic

Type: COB

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

Power: 13W

Light output tolerance +/- 10%

EPD

Tel. +34937366800 Web www.lamp.es

KOMBIC 100 SURFACE





K11SF2023RW830NBW


KOMBIC 100 SF 2000 IP23 WW RF WFL BK/WH

PHOTOMETRIC DATA:

K11SF2023RW830NBW $_{\eta}$ = 100% Imax = 1293 cd/klm UTE: CIE: 99 100 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU

KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH