KOMBIC 100 SURFACE



K11SF2023RW830NWB

- KOMBIC 100 SF 2000 IP23 WW RF WFL WH/BK

Description:

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.538 lm
 % :
 3000

 Plum:
 14,1W
 CRI :
 80

 Efficacy:
 109 lm/w
 MacAdam:
 3

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF2023RW830NWB

KOMBIC 100 SF 2000 IP23 WW RF WFL WH/BK


PHOTOMETRIC DATA:


K11SF2023RW830NWB $\eta = 100\%$


lmax = 1215 cd/klm


UTE: 1,00A

CIE: 94 97 99 100 100









KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH