KOMBIC 100 SURFACE



K11SF2023RW840NBB

- KOMBIC 100 SF 2000 IP23 NW RF WFL BK/BK



Description:

Finish: Matte black RAL 9011

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.491 lm
 ⁰K :
 4000

 Plum:
 14,1W
 CRI :
 80

 Efficacy:
 105,7 lm/w
 MacAdam:
 3

 UGR:
 <19</th>
 Power Supply:
 220-240V 50/60Hz

 Type:
 COB
 Gear:
 Electronic

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

Power: 13W

Light output tolerance +/- 10%



KOMBIC 100 SURFACE





K11SF2023RW840NBB


KOMBIC 100 SF 2000 IP23 NW RF WFL BK/BK

PHOTOMETRIC DATA:

K11SF2023RW840NBB η = 100% Imax = 1293 cd/klm UTE: CIE: 99 100 100 100 100







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH