KOMBIC 100 SURFACE



K11SF2023RW840NBW

KOMBIC 100 SF 2000 IP23 NW RF WFL BK/WH

Description:

Finish: Matte black RAL 9011

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.491 lm °K: 4000 Plum: 14,1W CRI: 80 Efficacy: 105,7 lm/w MacAdam: 3

UGR: <19 Power Supply: 220-240V 50/60Hz Type:

Gear:

Electronic

СОВ

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

Power: 13W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE





K11SF2023RW840NBW


KOMBIC 100 SF 2000 IP23 NW RF WFL BK/WH

PHOTOMETRIC DATA:

K11SF2023RW840NBW $\eta = 100\%$ Imax = 1293 cd/klm UTE: CIE: 99 100 100 100 100







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH