KOMBIC 100 SURFACE



K11SF2023RW927DMW

- KOM 100 SF 2000 IP23 9VWW RF WFL DA M/W

Description:

Finish: Matte Traffic white RAL 9016

Weight: 712 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.710 lm °K: 2700 Plum: 20W CRI: 90 Efficacy: 85,4 lm/w R9: 58 Type: СОВ 3 MacAdam:

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Power Supply:
 220-240V 50/60Hz

 Power:
 13W
 Gear:
 Adjustable DALI

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF2023RW927DMW

KOM 100 SF 2000 IP23 9VWW RF WFL DA M/W


PHOTOMETRIC DATA:


K11SF2023RW927DMW $\eta = 100\%$


lmax = 1215 cd/klm


UTE: 1,00A


CIE: 94 97 99 100 100




















Data according to regulations 2019/2020/EU and 2019/2015/EU

KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH