KOMBIC 100 SURFACE



K11SF2023RW930DWB

KOM 100 SF 2000 IP23 9WW RF WFL DA WH/BK

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.784 lm °K: 3000 Plum: 20W CRI: 90 Efficacy: 89,2 lm/w R9: 53 Type: СОВ 3 MacAdam:

LED Lifetime: 50.000 L70 B10 (Ta=25°C) 220-240V 50/60Hz Power Supply: Power: 13W Gear: Adjustable DALI

Light output tolerance +/- 10%

EPD

Data according to regulations 2019/2020/EU and 2019/2015/EU

KOMBIC 100 SURFACE



K11SF2023RW930DWB

KOM 100 SF 2000 IP23 9WW RF WFL DA WH/BK

PHOTOMETRIC DATA:

K11SF2023RW930DWB


 η = 100%


lmax = 1215 cd/klm


UTE: 1,00A


CIE: 94 97 99 100 100




















Data according to regulations 2019/2020/EU and 2019/2015/EU

KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH