# **Product datasheet**

### **KOMBIC 100 SURFACE**



### K11SF2023RW930DWW

- KOM 100 SF 2000 IP23 9WW RF WFL DA WH/WH



Description:

Finish: Matte Traffic white RAL 9016

Weight: 712 g

Installation: Recessed

### **TECHNICAL SPECIFICATIONS:**

Light output: 1.784 lm °K: 3000 Plum: 20W CRI: 90 Efficacy: 89,2 lm/w R9: 53 Type: СОВ MacAdam: 3

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Power Supply:
 220-240V 50/60Hz

 Power:
 13W
 Gear:
 Adjustable DALI

Light output tolerance +/- 10%



### **KOMBIC 100 SURFACE**



K11SF2023RW930DWW


## KOM 100 SF 2000 IP23 9WW RF WFL DA WH/WH


#### **PHOTOMETRIC DATA:**


lmax = 1215 cd/klm


UTE: 1,00A


CIE: 94 97 99 100 100




















Data according to regulations 2019/2020/EU and 2019/2015/EU

### **KOMBIC 100 SURFACE**



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

**Product code:**K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH