KOMBIC 100 SURFACE



K11SF2023RW940NWW

- KOMBIC 100 SF 2000 IP23 9NW RF WFL WH/WH



Description:

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.902 lm °K: 4000 Plum: 21,6W CRI: 90 Efficacy: 88 lm/w R9: 65 Type: СОВ MacAdam: 3

LED Lifetime: 50.000 L70 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 13W Gear: Electronic

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF2023RW940NWW

KOMBIC 100 SF 2000 IP23 9NW RF WFL WH/WH

PHOTOMETRIC DATA:

K11SF2023RW940NWW


 $\eta = 100\%$


Imax = 1215 cd/klm


UTE: 1,00A


CIE: 94 97 99 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH