#### **KOMBIC 100 SURFACE**

# LAMP Worktitude for light

#### K11SF2040OP930NMW



#### KOMBIC 100 SF 2000 IP43 9WW OP MA/WH

#### Description:

Suspended or ceiling mounting downlight model KOMBIC 100 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class I. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Weight: 498 g



Installation: Surface

#### **TECHNICAL SPECIFICATIONS:**

Light output: 1.392 lm °K: 3000 Plum: 13,4W CRI: 90 Efficacy: 103,9 lm/w 67 R9: Type: СОВ MacAdam: 3

**LED Lifetime:** 50.000 L80 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 12W Gear: Electronic

# Light output tolerance +/- 10%



















### **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU













## **KOMBIC 100 SURFACE**



ACCESORIES:

Suspension



**Product code:** K11SUADLATBK

duct code: Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH