

KOMBIC 100 SURFACE

K11SF2040OP940DMB



KOMBIC 100 SF 2000 IP43 9NW OP DA MA/BK


Description:

Suspended or ceiling mounting downlight model KOMBIC 100 SF by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Matte metallic interior reflector and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: metalized polycarbonate mate

Weight: 720 g


Installation: Surface



TECHNICAL SPECIFICATIONS:

Light output:	1.708 lm	°K :	4000
Plum:	20,4W	CRI :	90
Efficacy:	83,7 lm/w	R9 :	65
Type:	COB	MacAdam:	3
LED Lifetime:	50.000 L70 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	17W	Gear:	Adjustable DALI

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 SURFACE

K11SF2040OP940DMB

KOMBIC 100 SF 2000 IP43 9NW OP DA MA/BK

PHOTOMETRIC DATA :

