KOMBIC 100 SURFACE



K11SF2040WF927DBB

- KOMBIC 100 SF 2000 IP43 9VWW WFL DA B/B

Description:

Finition: Noir mat RAL 9011

SPÉCIFICATIONS TECHNIQUES:

 Flux lumineux:
 1.341 lm
 °K:
 2700

 Plum:
 14W
 IRC:
 90

 Efficacité:
 95,8 lm/w
 R9:
 57

UGR: <19 **Type**: COB

Durée de vie LED: >100.000h L90 B10 (Ta=25°C)

Puissance: 12,2W

Tolérance de flux lumineux +/- 10%

IP 43

EPD

OPTIONS PERSONNALISABLES:























KOMBIC 100 SURFACE





K11SF2040WF927DBB


KOMBIC 100 SF 2000 IP43 9VWW WFL DA B/B


DONNÉES PHOTOMÉTRIQUES:


K11SF2040WF927DBB η = 100% Imax = 1274 cd/klm UTE: CIE: 98 100 100 100 100

















KOMBIC 100 SURFACE



ACCESSOIRES:

Suspension



Code produit:

K11SUADLATBK



KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Code produit:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH