KOMBIC 100 SURFACE

K11SF2040WF927DWW



KOMBIC 100 SF 2000 IP43 9VWW WFL DA W/W

Description:

Suspended or ceiling mounting downlight model KOMBIC 100 SF by Lamp brand. Body made of white aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. White interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Weight: 712 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.476 lm °K: 2700 Plum: 20,3W CRI: 90 Efficacy: 72,7 lm/w R9: 57 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

17W Power:

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 100 SURFACE



K11SF2040WF927DWW

KOMBIC 100 SF 2000 IP43 9VWW WFL DA W/W

PHOTOMETRIC DATA:

K11SF2040WF927DWW


 η = 100%


Imax = 1265 cd/klm


UTE: 1,00A


CIE: 95 99 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH