KOMBIC 100 SURFACE



K11SF2040WF930NBW

KOMBIC 100 SF 2000 IP43 9WW WFL BK/WH

Description:

Matte black RAL 9011 Finish:



TECHNICAL SPECIFICATIONS:

Light output: 1.410 lm °K: 3000 Plum: 14W CRI: 90 Efficacy: 100,7 lm/w R9: 66

UGR: <19 Type: СОВ

LED Lifetime: >100.000h L90 B10 (Ta=25°C)

Power: 12,2W

Light output tolerance +/- 10%

ΙP 43

EPD

CUSTOM MADE OPTIONS:























Data according to regulations 2019/2020/EU and 2019/2015/EU

KOMBIC 100 SURFACE





K11SF2040WF930NBW


KOMBIC 100 SF 2000 IP43 9WW WFL BK/WH


PHOTOMETRIC DATA:


K11SF2040WF930NBW η = 100% lmax = 1274 cd/klmUTE: CIE: 98 100 100 100 100

















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

Description: K11SUADLATBK

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH