

KOMBIC 100 SURFACE

K11SF2040WF940DBB




KOMBIC 100 SF 2000 IP43 9NW WFL DA BK/BK

Description:

Suspended or ceiling mounting downlight model KOMBIC 100 SF by Lamp brand. Body made of black aluminum extrusion with reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Black interior reflector. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CRI90. Luminaire with electronic wiring Dali included. Insolation Class I. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte black RAL 9011

Weight: 712 g




Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	1.552 lm	°K :	4000
Plum:	20,3W	CRI :	90
Efficacy:	76,4 lm/w	R9 :	66
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	17W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 SURFACE

K11SF2040WF940DBB

KOMBIC 100 SF 2000 IP43 9NW WFL DA BK/BK

PHOTOMETRIC DATA :

K11SF2040WF940DBB
 $\eta = 100\%$
 $I_{max} = 1327 \text{ cd/klm}$
 UTE:
 CIE: 99 100 100 100 100

