KOMBIC 100 SURFACE



K11SF2040WF940DWW

-	KOMBIC	100 SF	2000 IP4	3 9NW WFI	DA WH/WH
---	---------------	--------	----------	-----------	----------

Description:

Finish: Matte white RAL 9010

TECHNICAL SPECIFICATIONS:

 Light output:
 1.519 lm
 oK:
 4000

 Plum:
 14W
 CRI:
 90

 Efficacy:
 108,5 lm/w
 R9:
 59

UGR: <19 **Type:** COB

LED Lifetime: >100.000h L90 B10 (Ta=25°C)

Power: 12,2W

Light output tolerance +/- 10%

IP 43

EPD

CUSTOM MADE OPTIONS:





















KOMBIC 100 SURFACE



K11SF2040WF940DWW

KOMBIC 100 SF 2000 IP43 9NW WFL DA WH/WH


PHOTOMETRIC DATA:


K11SF2040WF940DWW η = 100%


Imax = 1239 cd/klm


UTE: 1,00A


CIE: 96 99 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

Description: K11SUADLATBK

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH