KOMBIC 100 SURFACE



K11SF2523RF830DBW

- KOMBIC 100 SF 2500 IP23 WW RF FL DA B/W

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.082 lm °K: 3000 Plum: 20W CRI: 80 Efficacy: 93,4 lm/w R9: 80 UGR: <19 3 MacAdam:

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 19W

Light output tolerance +/- 10%

EPD

Tel. +34937366800 Web www.lamp.es


KOMBIC 100 SURFACE





K11SF2523RF830DBW


KOMBIC 100 SF 2500 IP23 WW RF FL DA B/W

PHOTOMETRIC DATA:









KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH