KOMBIC 100 SURFACE



K11SF2523RF830NBW

KOMBIC 100 SF 2500 IP23 WW RF FL BK/WH

Description:

Finish: Matte black RAL 9011

Weight: 680 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.082 lm °K: 3000 Plum: 21,6W CRI: 80 Efficacy: 110,4 lm/w R9: 80 UGR: <19 3

MacAdam: Type: СОВ 220-240V 50/60Hz

LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Electronic

Power Supply:

Power: 19W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE





K11SF2523RF830NBW


KOMBIC 100 SF 2500 IP23 WW RF FL BK/WH

PHOTOMETRIC DATA:

K11SF2523RF830NBW
η = 100%
Imax = 2279 cd/klm
UTE:
CIE: 100 100 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: Description:

K11SUADLATBK KOMBIC 100 SF ADAPT. LATERAL CABLE BK