## **KOMBIC 100 SURFACE**



K11SF2523RF840DBW

- KOMBIC 100 SF 2500 IP23 NW RF FL DA B/W

Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Surface

## **TECHNICAL SPECIFICATIONS:**

Light output: 2.185 lm °K: 4000 Plum: 20W CRI: 80 Efficacy: 102,2 lm/w R9: 80 UGR: <19 3 MacAdam:

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 19W

Light output tolerance +/- 10%

EPD

# **KOMBIC 100 SURFACE**





K11SF2523RF840DBW


KOMBIC 100 SF 2500 IP23 NW RF FL DA B/W

#### **PHOTOMETRIC DATA:**

K11SF2523RF840DBW  $\eta$  = 100% Imax = 2279 cd/klm UTE: CIE: 100 100 100 100 100







## **Product datasheet**

## **KOMBIC 100 SURFACE**



ACCESORIES:

Suspension



Product code: Description:

K11SUADLATBK KOMBIC 100 SF ADAPT. LATERAL CABLE BK