KOMBIC 100 SURFACE



K11SF2523RF840DWW

- KOMBIC 100 SF 2500 IP23 NW RF FL DA W/W

Description:

Finish: Matte white RAL 9010

Weight: 712 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.318 lm °K: 4000 Plum: 20W CRI: 80 Efficacy: 115,9 lm/w R9: 80 UGR: <19 3 MacAdam:

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 19W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE





K11SF2523RF840DWW


KOMBIC 100 SF 2500 IP23 NW RF FL DA W/W

PHOTOMETRIC DATA:

K11SF2523RF840DWW η = 100% Imax = 2200 cd/klm UTE: CIE: 98 99 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: Description:

K11SUADLATBK KOMBIC 100 SF ADAPT. LATERAL CABLE BK