KOMBIC 100 SURFACE



K11SF2523RW830DBB

- KOMBIC 100 SF 2500 IP23 WW RF WFL DA B/B



Description:

Finish: Matte black RAL 9011

Weight: 712 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.908 lm
 ⁰K :
 3000

 Plum:
 20W
 CRI :
 80

 Efficacy:
 95,4 lm/w
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 19W

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE





K11SF2523RW830DBB


KOMBIC 100 SF 2500 IP23 WW RF WFL DA B/B

PHOTOMETRIC DATA:

$$\label{eq:continuous} \begin{split} \text{K11SF2523RW830DBB} \\ \eta &= 100\% \\ \text{Imax} &= 1293 \text{ cd/klm} \\ \text{UTE:} \\ \text{CIE:} \ 99 \ 100 \ 100 \ 100 \ 100 \end{split}$$







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description: Product code:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK

Product code:K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH