KOMBIC 100 SURFACE



K11S

					Workittude for light	
F2523RW830DBW -	KOMBIC 100 SF	2500 IP23 WW RF WFL DA B/W				
	Description:					
	Finish. Many Many No. 1004					
	Finish: Matte black RAL 9011 Weight: 712 g					
	weight. / 12 g					
	Installation: Su	Installation: Surface				
	mstanation. Su	installation. Surface				
	TECHNICAL SPECIFICATIONS:					
	Light output:	1.908 lm	⁰K :	3000		
	Plum:	20W	CRI:	80		
	Efficacy:	95,4 lm/w	MacAdam:	3		
	Type: LED Lifetime:	COB		220-240V 50/60Hz		
	Power:	50.000 L70 B10 (Ta=25°C) 19W	Gear:	Adjustable DALI		
		1011				
	Light output tolerance +/- 10%					
	EPD					





KOMBIC 100 SURFACE





K11SF2523RW830DBW


KOMBIC 100 SF 2500 IP23 WW RF WFL DA B/W

PHOTOMETRIC DATA:

K11SF2523RW830DBW $_{\eta}$ = 100% $_{lmax}$ = 1293 cd/klm UTE: CIE: 99 100 100 100 100







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH