KOMBIC 100 SURFACE

K11SF2523RW830NMB

- KOMBIC 100 SF 2500 IP23 WW RF WFL MA/BK

Description:

Finish: metalized polycarbonate mate Weight: 680 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	2.081 lm	⁰K :	3000
Plum:	21,6W	CRI :	80
Efficacy:	96,3 lm/w	MacAdam:	3
Туре:	СОВ	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L70 B10 (Ta=25°C)	Gear:	Electronic
Power:	19W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Worktitude for light


KOMBIC 100 SURFACE

K11SF2523RW830NMB

KOMBIC 100 SF 2500 IP23 WW RF WFL MA/BK



PHOTOMETRIC DATA :



Product datasheet

KOMBIC 100 SURFACE

ACCESORIES :

Suspension



Product code: K11SUADLATBK

Description: KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH

Description: KOMBIC 100 SF ADAPT. LATERAL CABLE WH

Worktitude for light