KOMBIC 100 SURFACE



K11SF2523RW830NWB

Description:				
Finish: Matte	white RAL 9010			
Weight: 680 g				
Installation: S	Surface			
TECHNICAL SF	PECIFICATIONS:			
Light output:	2.081 lm	ο K :	3000	
Plum:	21,6W	CRI:	80	
Efficacy:	96,3 lm/w	MacAdam:	3	
Type:	COB	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	50.000 L70 B10 (Ta=25°C)	Gear:	Electronic	
Power:	19W			
Light output tole	rance +/- 10%			
EPD				
EPD				

CUSTOM MADE OPTIONS:



KOMBIC 100 SURFACE



K11SF2523RW830NWB

KOMBIC 100 SF 2500 IP23 WW RF WFL WH/BK


PHOTOMETRIC DATA:


K11SF2523RW830NWB $_{\eta}$ = 100%


lmax = 1215 cd/klm

UTE: 1,00A

CIE: 94 97 99 100 100







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH