# **KOMBIC 100 SURFACE**



K11SF2523RW840DBB

KOMBIC 100 SF 2500 IP23 NW RF WFL DA B/B



Description:

Matte black RAL 9011 Finish:

Weight: 712 g

Installation: Surface

# **TECHNICAL SPECIFICATIONS:**

Light output: 2.002 lm °K: 4000 20W Plum: CRI: 80 Efficacy: 100,1 lm/w MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L70 B10 (Ta=25°C) Gear: Adjustable DALI

Power: 19W

Light output tolerance +/- 10%



# **CUSTOM MADE OPTIONS:**



Data according to regulations 2019/2020/EU and 2019/2015/EU

# **KOMBIC 100 SURFACE**





K11SF2523RW840DBB


KOMBIC 100 SF 2500 IP23 NW RF WFL DA B/B

#### **PHOTOMETRIC DATA:**

K11SF2523RW840DBB  $\eta$  = 100% Imax = 1293 cd/klm UTE: CIE: 99 100 100 100 100







# **KOMBIC 100 SURFACE**



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH