KOMBIC 100 SURFACE



ν	CEN	523R\	NIO AC	DAMA
n i i	OFZ:	りとうにい	/V 04L	ואוטוטנ

_	KOMBIC	100 9	SF 2500	IP23 NW	RF WFI	DA M/W

KOMBIC 100 SF 2500 IP23 NW RF WFL DA M/W						
Description:						
Finish: metaliz	red polycarbonate mate					
Weight: 712 g	ed polycarbonate mate					
g						
Installation: Su	ırface					
TECHNICAL SPI	ECIFICATIONS:					
Light output:	2.184 lm	°К :		4000		
Plum:	20W	CRI:		80		
Efficacy:	109,2 lm/w	MacAdar		3		
Туре:	СОВ	Power S	upply:	220-240V 50/60Hz		
LED Lifetime:	50.000 L70 B10 (Ta=25°C)	Gear:		Adjustable DALI		
Power:	19W					
Light output toler	ance +/- 10%					
EPD						
CUSTOM MADE	OPTIONS:					
- Joi Jim made						



KOMBIC 100 SURFACE



K11SF2523RW840DMW

KOMBIC 100 SF 2500 IP23 NW RF WFL DA M/W


PHOTOMETRIC DATA:


K11SF2523RW840DMW η = 100%


lmax = 1215 cd/klm


UTE: 1,00A

CIE: 94 97 99 100 100









KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH