KOMBIC 100 SURFACE



K11SF2523RW840DWW

- KOMBIC 100 SF 2500 IP23 NW RF WFL DA W/W



Description:

Finish: Matte white RAL 9010

Weight: 712 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 2.184 lm
 %:
 4000

 Plum:
 20W
 CRI:
 80

 Efficacy:
 109,2 lm/w
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L70 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 19W

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



KOMBIC 100 SURFACE



K11SF2523RW840DWW

KOMBIC 100 SF 2500 IP23 NW RF WFL DA W/W


PHOTOMETRIC DATA:


K11SF2523RW840DWW η = 100%


lmax = 1215 cd/klm


UTE: 1,00A

CIE: 94 97 99 100 100









KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH