KOMBIC 100 SURFACE



K11SF2523RW840NBB

KOMBIC 100 SF 2500 IP23 NW RF WFL BK/BK



Description:

Finish: Matte black RAL 9011

Weight: 680 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 2.002 lm
 %K:
 4000

 Plum:
 21,6W
 CRI:
 80

 Efficacy:
 92,8 lm/w
 MacAdam:
 3

Type: COB **Power Supply:** 220-240V 50/60Hz

Gear:

Electronic

LED Lifetime: 50.000 L70 B10 (Ta=25°C)

Power: 19W

Light output tolerance +/- 10%

EPD

CUSTOM MADE OPTIONS:

RAW

KOMBIC 100 SURFACE





K11SF2523RW840NBB


KOMBIC 100 SF 2500 IP23 NW RF WFL BK/BK

PHOTOMETRIC DATA:

K11SF2523RW840NBB η = 100% lmax = 1293 cd/klm UTE: CIE: 99 100 100 100 100







KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code:

K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code:

K11SUADLATWH

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH