Product datasheet


KOMBIC 100 DOWNLIGHT

K11SQ1540OP940NMW



Description:

Square recessed downlight model KOMBIC 100 SQ 1500 IP40 9NW OP MA/WH, LAMP brand. Reflector made of polycarbonate. Matte metallic interior reflector and frame in white finish, opal diffuser and injected aluminium dissipator. Model for LED COB, with neutral white colour temperature and control gear included. IP43 protection rating. Insulation class II. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: metalized polycarbonate mate


Weight: 392 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.283 lm	⁰К:	4000
Plum:	13,4W	CRI :	90
Efficacy:	95,8 lm/w	R9 :	66
Туре:	СОВ	MacAdam:	3
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60H
Power:	12W	Gear:	Electronic

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Worktitude for light

KOMBIC 100 DOWNLIGHT

K11SQ1540OP940NMW

KOMBIC 100 SQ 1500 IP43 9NW OP MA/WH



PHOTOMETRIC DATA :

