KOMBIC 100 DOWNLIGHT


K11SQ1540WF927DBB



KOMBIC 100 SQ 1500 IP43 9VWW WFL DA B/B

Description:

Square recessed downlight model KOMBIC 100 SQ 1500 IP40 9VWW WFL DA BK/BK, LAMP brand. Reflector made of polycarbonate. Interior reflector and frame in black finish, injected aluminium dissipator. Model for LED COB, with 2700K colour temperature, CRI 90 and control DALI gear included. IP20 protection rating. Optic Wide Flood to achieve a controlled light distribution and low glare level, less than UGR 17. Insulation class II. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte black RAL 9011

Weight: 442 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.031 lm °K: 2700 Plum: 13,4W CRI: 90 Efficacy: 76,9 lm/w R9: 60 UGR: <19 MacAdam: 3

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

12W Power:

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













KOMBIC 100 DOWNLIGHT



K11SQ1540WF927DBB

KOMBIC 100 SQ 1500 IP43 9VWW WFL DA B/B

PHOTOMETRIC DATA:

K11SQ2040WF830NBB η = 100% Imax = 1269 cd/klm UTE: CIE: 98 100 100 100 100

