KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11SQ1540WF927NBW - **KOMBIC 100 SQ 1500 IP43 9VWW WFL BK/WH**

Description:

Finish: Matte black RAL 9011

TECHNICAL SPECIFICATIONS:

Light output:	1.002 lm	**ºK :**	2700
Plum:	10W	**CRI :**	90
Efficacy:	100,2 lm/w	**R9 :**	57
UGR:	<19		
LED Lifetime:	>100.000h L90 B10 (Ta=25ºC)		
Power:	8,5W		

Light output tolerance +/- 10%

IP
20 INT
43 EXT

EPD

CUSTOM MADE OPTIONS:

1-10V | | | | ↑lm | LED RETAIL | | PUSH | TRIAC | K

KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11SQ1540WF927NBW   KOMBIC 100 SQ 1500 IP43 9VWW WFL BK/WH

PHOTOMETRIC DATA :

K11SQ1540WF927NBW

η = 100%

Imax = 1274 cd/klm

UTE:

CIE: 98 100 100 100 100

180°

90°   90°

0°

alpha = 57,1º

100%
75%
50%
25%

BACK   FRONT

50,1 %   50,1 %

-8H   -4H   0H   4H   8H

Melanopic Lux Ratio: 0.495

3000K 2500K 2000K
4000K   1667K
6000K
10000K

5 4
6   3
7   2
8   1
9   16
10   15
11   14
12 13

Rf
140
130   1 - Limits on the Planckian locus
120
110
100   Rg
90
80
70   2 - Limits for practical sources   **Rf 91.6 - Rg 99.8**
60
50 60 70 80 90 100

03-06-2025

Data according to regulations 2019/2020/EU and 2019/2015/EU