KOMBIC 100 DOWNLIGHT


K11SQ1540WF930NWW



KOMBIC 100 SQ 1500 IP43 9WW WFL WH/WH

Description:

Square recessed downlight model KOMBIC 100 SQ by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CR90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low glare level, less than UGR 17. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Weight: 385 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Plum: 13,7W °K: 3000 UGR: <19 CRI: 90 Type: COB R9: 62 LED Lifetime: 50.000 L80 B10 (Ta=25°C) MacAdam: 3

Power: 12W Power Supply: 220-240V 50/60Hz

> Gear: Electronic



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU











