Product datasheet

KOMBIC 100 DOWNLIGHT

K11SQ2040OP927NWW

KOMBIC 100 SQ 2000 IP43 9VWW OP WH/WH

Description:

Square recessed downlight model KOMBIC 100 SQ by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Weight: 392 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.602 lm	**ºK :**	2700
Plum:	19,1W	**CRI :**	90
Efficacy:	83,9 lm/w	**R9 :**	61
Type:	COB	**MacAdam:**	3
LED Lifetime:	50.000 L70 B10 (Ta=25ºC)	**Power Supply:**	220-240V 50/60Hz
Power:	17W	**Gear:**	Electronic

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:

KOMBIC 100 DOWNLIGHT

K11SQ2040OP927NWW **KOMBIC 100 SQ 2000 IP43 9VWW OP WH/WH**

PHOTOMETRIC DATA :

K11SQ2040OP927NWW

η = 100%

Imax = 766 cd/klm

UTE: 1,00B

CIE: 76 95 99 100 100









LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU