


# KOMBIC 100 DOWNLIGHT

K11SQ20400P927NWW



## KOMBIC 100 SQ 2000 IP43 9VWW OP WH/WH

### Description:

Square recessed downlight model KOMBIC 100 SQ by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L70 B10. With IP43 degree of protection. Group 0 photobiological safety.

**Finish:** Matte white RAL 9010


**Weight:** 392 g

**Installation:** Recessed

### TECHNICAL SPECIFICATIONS:

<b>Light output:</b>	1.602 lm	<b>°K :</b>	2700
<b>Plum:</b>	19,1W	<b>CRI :</b>	90
<b>Efficacy:</b>	83,9 lm/w	<b>R9 :</b>	61
<b>Type:</b>	COB	<b>MacAdam:</b>	3
<b>LED Lifetime:</b>	50.000 L70 B10 (Ta=25°C)	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Power:</b>	17W	<b>Gear:</b>	Electronic

*Light output tolerance +/- 10%*



### CUSTOM MADE OPTIONS:



# KOMBIC 100 DOWNLIGHT

K11SQ20400P927NWW

KOMBIC 100 SQ 2000 IP43 9VWW OP WH/WH

## PHOTOMETRIC DATA :

