KOMBIC 100 DOWNLIGHT




K11SQ2040OP930NWW

KOMBIC 100 SQ 2000 IP43 9WW OP WH/WH



Description:

Square recessed downlight model KOMBIC 100 SQ by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K with CRI90. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 50.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD® available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte white RAL 9010

Weight: 392 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Plum: 19,1W °K: 3000 Type: СОВ CRI: 90 **LED Lifetime:** 50.000 L80 B10 (Ta=25°C) R9: 67 Power: 17W MacAdam: 3

> Power Supply: 220-240V 50/60Hz

Gear: Electronic



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU









