

KOMBIC 100 DOWNLIGHT

K11SQ20400P9TWDRW




KOMBIC 100 SQ 2000 IP43 TW OPAL DA BR/WH

Description:

Square recessed downlight model KOMBIC 100 SQ by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Shiny metalized interior reflector and frame in white finish and optical film. Heatsink made of die-cast aluminium. COB LED, with dynamic white colour temperature (2700-6500K) with CRI90. Luminaire with electronic wiring Dali included. Insolation Class II. Lifetime: 70.000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: BRILLIANT METALLIC POLYCARBONATE**Weight:** 550 g**Installation:** Recessed**TECHNICAL SPECIFICATIONS:**

Light output:	1.335 lm	°K :	2700-6500
Plum:	20,7W	CRI :	90
Efficacy:	64,5 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	70.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	16W		

Light output tolerance +/- 10%

KOMBIC 100 DOWNLIGHT

K11SQ20400P9TWDRW

KOMBIC 100 SQ 2000 IP43 TW OPAL DA BR/WH

PHOTOMETRIC DATA :

